


SPHERICAL BEARINGS - GEZ...ES SERIES

ORDER CODE	P Ø(mm)	D Ø(mm)	A (mm)	S (mm)	MOVEMENT ANGLE (α°)	DYNAMIC LOAD (kn)	STATIC LOAD (kn)
GEZ12ES	12.7	22.225	11.1	9.525	6	13.7	41.5
GEZ15ES	15.87	26.988	13.894	11.91	6	22	65.5
GEZ19ES	19.05	31.75	16.662	14.27	6	31.5	95
GEZ22ES	22.22	36.513	19.431	16.66	6	42.5	127
GEZ25ES	25.4	41.275	22.225	19.05	6	54	163
GEZ31ES	31.75	50.8	27.762	23.8	6	86.5	260
GEZ34ES	34.92	55.563	30.15	26.18	6	102	310
GEZ38ES	38.1	61.913	33.325	28.57	6	122	365
GEZ44ES	44.45	71.438	38.887	33.32	6	170	510
GEZ50ES	50.8	80.963	44.45	38.1	6	224	670
GEZ57ES	57.15	90.488	50.013	42.85	6	280	850
GEZ63ES	63.5	100.01	55.55	47.62	6	355	1060
GEZ69ES	69.85	111.12	61.112	52.37	6	375	1250
GEZ76ES	76.2	120.65	66.675	57.15	6	500	1500
GEZ82ES	82.55	130.17	72.238	61.9	6	600	1760
GEZ88ES	88.9	139.7	77.775	66.67	6	680	2040
GEZ95ES	95.25	149.22	83.337	71.42	6	780	2360
GEZ101ES	101.6	158.75	88.900	76.20	6	900	2650
GEZ107ES	107.95	168.27	94.463	80.95	6	1000	3000
GEZ114ES	114.3	177.8	100.00	85.72	6	1120	3400
GEZ120ES	120.65	187.32	105.56	90.47	6	1250	3750
GEZ127ES	127	196.85	111.12	95.25	6	1400	4150
GEZ152ES	152.4	222.25	120.65	104.77	5	1730	5200


SPHERICAL PLAIN BEARING
METRIC ► IMPERIAL EQUIVALENT
MAINTENANCE VERSION
STEEL / STEEL COUPLING
TEMPERATURE RANGE: -50°C ► +180°C



SPHERICAL BEARINGS - GEZ...ES-2RS SERIES

ORDER CODE	P Ø(mm)	D Ø(mm)	A (mm)	S (mm)	MOVEMENT ANGLE (α°)	DYNAMIC LOAD (kn)	STATIC LOAD (kn)
GEZ19ES-2RS	19.05	31.75	16.662	14.27	6	31.5	95
GEZ22ES-2RS	22.22	36.513	19.431	16.66	6	42.5	127
GEZ25ES-2RS	25.4	41.275	22.225	19.05	6	54	163
GEZ31ES-2RS	31.75	50.8	27.762	23.8	6	86.5	260
GEZ34ES-2RS	34.92	55.563	30.15	26.18	6	102	310
GEZ38ES-2RS	38.1	61.913	33.325	28.57	6	122	365
GEZ44ES-2RS	44.45	71.438	38.887	33.32	6	170	510
GEZ50ES-2RS	50.8	80.963	44.45	38.1	6	224	670
GEZ57ES-2RS	57.15	90.488	50.013	42.85	6	280	850
GEZ63ES-2RS	63.5	100.01	55.55	47.62	6	355	1060
GEZ69ES-2RS	69.85	111.12	61.112	52.37	6	375	1250
GEZ76ES-2RS	76.2	120.65	66.675	57.15	6	500	1500
GEZ82ES-2RS	82.55	130.17	72.238	61.9	6	600	1760
GEZ88ES-2RS	88.9	139.7	77.775	66.67	6	680	2040

SPHERICAL PLAIN BEARING
METRIC / IMPERIAL EQUIVALENT
MAINTENANCE VERSION
FITTED WITH PROTECTION RINGS
STEEL / STEEL COUPLING
TEMPERATURE RANGE: -20°C ► +90°C



PLEASE NOTE: TO AVOID DAMAGE / LOSS OF THE PROTECTION RINGS (-2RS), DO NOT ALLOW THE INNER BALL TO ROTATE OUT OF THE EXTERNAL HOUSING.